



Applications

- alkitronic® M hand torque multiplier for energy independent precise tightening and loosening of heavy-duty bolt connections.
- Torques from 200 Nm up to 50,000 Nm.
- The ideal torque tool in high explosion-risk areas
- alkitronic® M provide safe, economic, problem-free operation. They replace impact wrenches, pipe extensions and other inadequate methods.

Advantages

- Maintenance-free, compact and robust design. They improve onthe-job safety and have short assembly times.
- Low energy input high torque transfer.
- Integrated anti wind-up ratchet allows jobs to be performed easily, efficiently and safely.

alkitronic° specials


- The components of the *alkitronic*® power gears are manufactured using a high-precision chipless process in order to ensure the highest possible operational demands with lowest wear.
- The shearing pin built into the drive shaft protects against input overload.



Technical Data: Modell H	(without rachet	and HG	(with rachet)
--------------------------	-----------------	---------------	---------------

Туре			H10	H15	HG10	HG15	HG20	HG30	HG40	HG50	HG60	HG80
Torque up to (approx.)*		Nm	1400	1400	1400	1400	3500	5000	6000	8000	11500	50000
Square drive	В		1/2" / 3/4"	1″	1/2" / 3/4"	1″	1″	11/2"	11/2"	11/2"	11/2"	2 1/2"
Reduction ratio			4	4	4	4	16	18	20	24	28	180
Diameter	D	mm	85	85	85	85	85	98	109	133	173	275
Height	Н	mm	180	200	180	200	235	250	280	280	290	360
Weight (approx.)		kg	3,5	4	3,5	4	5	6,5	7	11	19	58

^{*)} When loosening a bolted connection, up to 20% higher torque may be required (loosening torque). We will gladly advise you in detail.



Connector:

1/2" internal square socket - 3/4" external square socket

Specifications

Torque Multiplier input via:

3/4" internal square socket torque wrench or conventional ratchets external hexagonal socket SW 36 mm.

Handwheel - for rough turning loose bolts/nuts.

alkitronic® manual torque multipliers are supplied with a support foot (DMA) as standard version.

Forsupportrings, backstops, ratchets, torque wrenches, and other components, please see our *alkitronic*® catalog of accessories.

alki TECHNIK GmbH reserves the right to change specifications without prior notice.



 $\textit{alkitronic} \, {}^{\text{\tiny{@}}} \, {}^{\text{\tiny{e}}} \, \text{power gear components}$



alkitronic® M operating on electricity pylons. Accurate tightening via torque wrench.



alkitronic® products Made in Germany by

alki TECHNIK GmbH

Development, Production and Distribution of Bolting Systems

Unterlettenweg 4 D-85051 Ingolstadt

fon +49 841 97499-0 fax +49 841 97499-90

info@alkitronic.com www.alkitronic.com